

Trusted, secure ID issuance



The complete range of ID card printers,
all with security built in.

HoloKote® - inbuilt visual security

HoloKote - added visual **security** at no extra cost

HoloKote, patented by Magicard, is a secure watermark that is frosted into the clear protective overcoat of the normal print process using standard consumables (ribbons and cards). It can be visually verified when the card is tilted in the light.



HoloPatch® enhanced visual **security**

HoloPatch cards have a highly reflective gold 'super diffuser' seal. When the HoloKote watermark is printed onto the seal, it becomes a distance visible security mark enabling security verification from a range of six feet or more.



Your logo as a customised **security** watermark


With the Magicard Rio Pro, the HoloKote watermark can be customised to an organisation's logo, or some other unique security design. This innovative security option is available by special order and the short lead time makes it possible for customers to start producing secure ID cards in far less time than is required by a custom holographic overlamine solution, and at a fraction of the cost.



Our promise to keep you printing

The best **support** in the industry

Magicard's online and telephone support sets the benchmark for the ID printer industry. A comprehensive online portal with self-help, training videos and up-to-date downloadables is backed up by a global network of highly-trained technical support engineers, all available to take your call.



The best **warranty** in the industry

The reliability of our well established print engine enables us to offer some of the best warranty terms in the industry. Both the Rio Pro and Prima 4 are backed with a 3-year UltraCoverPlus warranty that includes:

- **Replacement of a damaged printhead** no matter what the cause of failure
- **A hot-swap loaner** if a printer is shipped to our service centre for repair

The Pronto and Enduro3E printers are backed with 2 and 3 year depot warranties respectively.







Pronto

Direct-to-card printer



ID card printing made easy



Incredibly easy to use with drop-in dye film and hand-fed card loading, the Pronto includes the HoloKote® visual security system and can print colour, monochrome or rewritable cards.

Its plug-and-play setup and compact footprint are ideal for portability and lower volume card printing.

Printer

Print technology	300 dpi dye sublimation/rewritable.
Card thickness	0.51mm to 1.02mm (20 mil to 40 mil).
Printer interface	USB rev.1.1/USB 2.0.
Drivers/software	Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012 and Mac OS X 10.9.0 upwards.
Dimensions	W 215mm x H 233mm x D 270mm (W 8.4" x H 9.1" x D 10.6").
Weight	4.4 kg/9.7 lb.
Operating environment	Sheltered office environment 10°C - 30°C (50°F - 85°F).

Security

Gold seal	HoloPatch® card stock – ordered separately.
Magnetic stripe encoding	HiCo and LoCo encoder ISO std. 7811.
Smart card encoding	Contact chip, MIFARE®, DESFire®, iClass® options.

Security watermark HoloKote (4 standard designs).



Features

Standard



Optional








Enduro3E

Direct-to-card printer



The World's most reliable card printer



Robust, durable and reliable, the Enduro3E is perfect for schools, colleges and medium sized businesses that print up to 10,000 cards per year. The latest edition of this established ID card printing platform now includes Ethernet as standard and a 3 year warranty. When it comes to secure and reliable ID card printing, you can trust the Enduro3E to deliver.


Printer

Print technology	300 dpi dye sublimation/rewritable.
Card thickness	0.51mm to 1.02mm (20 mil to 40 mil).
Printer interface	USB rev.1.1/USB 2.0, Ethernet.
Drivers/software	Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012 and Mac OS X 10.9.0 upwards.
Dimensions	W 206mm x H 233mm x D 453mm (W 8.1" x H 9.2" x D 17.8").
Weight	5.5 kg/12 lb.
Operating environment	Sheltered office environment 10°C - 30°C (50°F - 85°F).

Security

Gold seal	HoloPatch® card stock – ordered separately.
Magnetic stripe encoding	HiCo and LoCo encoder ISO std. 7811.
Smart card encoding	Contact chip, MIFARE®, DESFire®, iClass® options.

Security watermark HoloKote (4 standard designs).




Features

Standard



Optional



The industry standard for secure ID card printing



150 1HR

Printing speed
>150 full colour
cards per hour

100/70

Card capacities
100 card input
70 card output

3 YEAR
UCP

Warranty
3 year UltraCoverPlus
with hot swap printer

CUSTOM
LOGO

Visual security
Standard or Custom
HoloKote® watermark

Windows | OS X

Operating systems
Windows and Mac OS
compatible

The Rio Pro sets the standard for secure ID card printing. Its high capacity card hoppers and fast print engine can reliably produce large volumes of secure cards day in, day out.

The inbuilt Custom HoloKote® visual security system protects cards from fraud while Ethernet connectivity, a suite of encoding options and a comprehensive SDK deliver flexibility, security and reliability to your desktop.

Features

Standard



Optional




Printer

Print technology	300 dpi dye sublimation/rewritable.
Card thickness	0.51mm to 1.02mm (20 mil to 40 mil).
Printer interface	USB rev.1.1/USB 2.0, Ethernet.
Drivers/software	Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012 and Mac OS X 10.9.0 upwards.
Dimensions	W 220mm x H 250mm x D 470mm (W 8.6" x H 9.8" x D 18.5").
Weight	4.9 kg/10.8 lb.
Operating environment	Sheltered office environment 10°C - 30°C (50°F - 85°F)

Security

Gold seal	HoloPatch® card stock – ordered separately.
Magnetic stripe encoding	HiCo and LoCo encoder ISO std. 7811.
Smart card encoding	Contact chip, MIFARE®, DESFire®, iClass® options. Other encoders available.

Security watermark	HoloKote (5 standard designs).
--------------------	--------------------------------



Customised watermark	Custom HoloKote® - Grid or full card pattern.
----------------------	-----------------------------------------------



Photo quality printing and lamination in a desktop package



FIPS-201 certified for the personalisation of US Government credentials, the Prima 4 provides the most reliable, robust solution for instant issuance in a compact package.

Using retransfer printing technology, the Prima 4 produces cards with a photo quality comparable to offset lithographic printing.


Optional UV printing, holographic lamination and multiple encoding options add an additional layer of security and durability.

Features

Standard



Optional




Printer

Print technology	300 dpi retransfer with 600 dpi option.
Card thickness	0.25mm to 1.00mm (10mil to 40mil).
Printer interface	USB 2.0, Ethernet.
Drivers/software	Windows 2000 Professional (SP4), XP (SP2, SP3), Vista (SP1), Windows Server 2003 R2 SP2, Server 2008, 2012, Windows 7, 8, 10 (32 and 64 bit).
Dimensions	343mm W x 320mm H x 330mm L (13.5" W x 12.6" H x 13" L).
Weight	15.5kg (34.1lbs).
Operating environment	Sheltered office environment 10°C - 30°C (50°F - 85°F).

Security and durability


Printer security	Kensington lock, electronic lock for hopper and door, security ribbon erase.
Magnetic stripe encoding	HiCo encoder ISO std. 7811
Smart card encoding	Contact chip, MIFARE®, DESFire®, iClass® options. Others available.

UV




Available with YMCK-UV film only

Standard laminates



Customised laminates



Rio PRO Secure

Specialist printer

Secure your localised credential issuance



The Rio Pro Secure features an opaque, lockable input hopper to secure blank cards. A secondary lock prevents the printer from being opened by unauthorised personnel and secures the opaque output stacker cover.

Rio PRO Xtended

Specialist printer

Xtend your card printing capability



An adaptation of the Rio Pro print platform, with an extra large hopper and stacker, the Rio Pro Xtended prints oversized cards up to 140mm long for ticketing, accreditation and events.

Printing	Pronto	Enduro3E	Rio Pro	Prima 4
Print technology	Dye sublimation/rewritable	Dye sublimation/rewritable	Dye sublimation/rewritable	Retransfer
Feed system	Manual	Manual/automatic	Manual/automatic	Automatic
Card capacity: standard input hopper / output stacker	100/30	100/30	100/70	100/100
Extra capacity input hopper (200 cards)	—	—	3652-0122	—
Extra capacity output stacker (130 cards)	—	—	3652-0124	—
Single-sided printer	3649-0001	3633-3001	3652-0001	Prima 401
Double-sided printer	—	3633-3021	3652-0021	Prima 402
Upgrade (single to double-sided)	—	3633-0052	3633-0052	—
Laminator	—	—	—	Prima 451 (Uno) / Prima 452 (Duo)
Encoding / variants				
Magnetic stripe encoding ISO 7811 - tracks 1, 2 & 3	3649-0002 (Pronto Mag)	3633-3002 (Enduro3E Uno Mag)	3652-0002 (Rio Pro Uno Mag)	—
Smart card encoding (contact chip, MIFARE®, DESFire® & iClass®)	3649-0003 (Pronto Smart)	3633-3022 (Enduro3E Duo Mag)	3652-0022 (Rio Pro Duo Mag)	Prima 403 (Prima Duo Mag)
	—	3633-3005 (Enduro3E Uno Smart)	3652-0003 (Rio Pro Uno Smart)	Prima 406 (Prima Uno Smart)
	—	3633-3025 (Enduro3E Duo Smart)	3652-0023 (Rio Pro Duo Smart)	Prima 415 (Prima Duo Smart)
Other smart card configurations available on request	—	—	●	●
Connectivity and drivers				
USB connection	●	●	●	●
Ethernet connection	—	●	●	—
Windows XP, Vista, 7, 8, 10 (32/64bit) Windows server	●	●	●	●
2003 R2 SP2, 2008, 2012 and Mac OS X 10.9.0 upwards	—	—	—	—
Warranty				
2 years limited	●	—	—	—
3 years limited	—	●	—	—
3 years UltraCoverPlus - (with hot-swap loaner)	—	—	●	●
Printhead guarantee	—	—	3 years	Lifetime
Visual security				
HoloKote watermark - standard design	x4	x4	x5	—
HoloKote watermark - custom design	—	—	●	—
UV film	—	—	—	●
HoloPatch cards	●	●	●	●
Standard overlamine - patch and continuous	—	—	—	●
Custom overlamine - patch and continuous	—	—	—	●
Print speed				
Colour	35 seconds per card	>100 cards per hour	>150 cards per hour	>100 cards per hour
Monochrome	7 seconds per card	>500 cards per hour	>500 cards per hour	—
Card thickness				
mm	0.51 to 1.02	0.51 to 1.02	0.51 to 1.02	0.25 to 1.00
mil	20 to 40	20 to 40	20 to 40	10 to 40
Dimensions				
Width x height x depth : mm	215 x 233 x 270	206 x 233 x 453	220 x 250 x 470	343 x 320 x 330
Width x height x depth : inch	8.4 x 9.1 x 10.6	8.1 x 9.2 x 17.8	8.6 x 9.8 x 18.5	13.5 x 12.6 x 13
Weight : kg	4.4	5.5	4.9	15.5
Weight : lb	9.7	12	10.8	34
Maintenance				
Cleaning kit	CK1	3633-0053	3633-0053	E9887

● = Standard ● = Option

Pronto, Enduro3E and Rio Pro printer dye films	Capacity	Product code	Prima 4 printer films	Product code	Details	Capacity
Colour dye film with overcoat panel (YMCKO)	100	MA100YMCKO	Prima 4 film sets	Prima 431	YMCK colour dye film and retransfer film sets (x5 sets)	1000 images per set
Colour dye film with overcoat panel (YMCKO)	300	MA300YMCKO		Prima 431/S	YMCK colour dye film and retransfer film set (x1 set)	1000 images
Colour dye film with black panel on reverse (YMCKOK)	250	MA250YMCKOK	Prima 4 dye film	Prima 433	YMCKK colour dye film with black panel on reverse	750 images
Black resin dye film with overcoat panel (KO)	600	MA600KO		Prima 434	YMCK-UV colour dye film with UV panel	750 images
Monochrome resin dye film - Black	1000	MA1000K-Black		Prima 435	YMCKO-PO dye film with peel-off panel	750 images
Monochrome resin dye film - White	1000	MA1000K-White	Prima 4 retransfer film	Prima 436	Retransfer film	1000 images
Monochrome resin dye film - Silver	1000	MA1000K-Silver	Prima 4 patch laminate film	Prima 462	Clear patch laminate 0.6mil	600 patches
Monochrome resin dye film - Gold	1000	MA1000K-Gold		Prima 463	Clear patch laminate 0.6mil with chip cutout	600 patches
Monochrome resin dye film - Blue	1000	MA1000K-Blue		Prima 464	Clear patch laminate 1.0mil	600 patches
Monochrome resin dye film - Red	1000	MA1000K-Red		Prima 465	Clear patch laminate 1.0mil with chip cutout	600 patches
Monochrome resin dye film - Green	1000	MA1000K-Green	Prima 4 overlay film	Prima 461	OVD 'snowflake' design film	1000 overlays
				Prima 466	Clear OVD film	1000 overlays
			Prima 4 custom overlay/patch	Prima 468	Set up charge for custom overlay film/patch laminate	Contact us
				Prima 467-patch	Custom design holographic patch 0.6mil	600 patches
				Prima 467-overlay	Custom design holographic overlay	1000 overlays



Important: Printer warranty is subject to the observance of specific conditions of use and maintenance, including printer registration and the use of certified 'Original MagiCard' dye films.

Global offices



Headquarters and manufacturing centre

Hampshire Road,
Weymouth,
Dorset DT4 9XD,
United Kingdom

Tel: +44 (0)1305 47 00 00

Email: info@magiCARD.com



Americas sales and support center

6724 Suite A,
185th Avenue NE,
Redmond, WA 98052,
USA

Toll free: 877 236 0933

Tel: +1 (425) 556 9708

Email: USsales@magiCARD.com



China sales and support centre

Room 902 Zhonghuang Tower,
No.1007 Second Zhongshan Road (S)
Xuhui District Shanghai 2000030,
PRC.

Tel: +86 21 6457 3509

Email: china@magiCARD.com



Middle East sales and support centre

4WB (West Wing) Office - 652,
Dubai Airport Free Zone,
PO Box: 54974, Dubai,
United Arab Emirates

Tel: +971 4 260 2930

Email: uae@magiCARD.com

Legal

MagiCard, HoloKote, Custom HoloKote, HoloPatch, Rio Pro, Enduro3E, Pronto and Prima4 are trademarks or registered trademarks of MagiCard Ltd. All other trademarks, brand names, or product names belong to their respective holders.

The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.